




CEJN

The Global Quick Connect Specialist

High Quality Quick Connect Components for All Media





Content



04

CEJN PRESENTATION

The CEJN Group provides the global market with high performance quick connect components and systems for hydraulic, pneumatic, fluid, and gas applications. The development of new products focuses on innovative solutions with total customer satisfaction.



07

PNEUMATICS

CEJN's pneumatic product line includes the world's best-performing quick couplings, blowguns, polyurethane hose, lightweight and heavy-duty hose and cable reels, and accessories.



13

GAS

CEJN's gas product line meets the extra stringent safety demands of gas applications. The products have an automatic safety-locking feature and double seal functions for extra safety protection, plus color coding on both the couplings and nipples.



14

BREATHING AIR

A wide variety of quick connect couplings is included in CEJN's breathing air lineup that is directly involved in saving lives. CEJN breathing air couplings have a high-flow rate and a broad connection range and require only minimal force to connect.



16

FLUIDS

CEJN's fluid coupling lineup includes over 15 series of high-quality products in both valved and valveless designs for low- and medium-pressure applications, with maximum working pressures up to 200 bar (2900 PSI).



20

HYDRAULICS

Low- and medium pressure styles with operating pressures up to 320 bar (4640 PSI) for both industrial and mobile use are offered in the CEJN hydraulic coupling range. Product features include heavy-duty designs, hardened steel constructions, extra security locking, flat-face designs, and one-hand-operated connections.



22

HIGH-PRESSURE HYDRQAULICS

CEJN offers quick couplings with operating pressures up to 3000 bar (43,500 PSI), porting blocks, pressure gauges, and adapters for a wide range of demanding applications in high-pressure hydraulics.



24

WEO PLUG-IN

CEJN WEO Plug-In threadless hose fittings simply "plug in" to hydraulic systems. WEO fittings are available in sizes 1/4" through 1" with maximum working pressures of up to 350 bar (5075 PSI).



26

MULTI & AUTO

CEJN multiple connections enable several fluid lines to be ganged and connected and disconnected in an instant. Designed for modular systems, two styles are offered: Automation couplings and the Multi-Snap system.



Exiting future for CEJN and its customers

CEJN stands ready to take on the future with new challenges and innovative products. CEJN will continue to provide customers with quality products for as long as there is a need for quick connect products.

Quick Connect Products of Choice

– a reliable partner for quality solutions, yesterday, today and tomorrow

CEJN has successfully manufactured couplings for air and liquid applications for close to 50 years. During this time the range has expanded from just a few products to now comprise several thousand items, all based on customer requests and new market standards.

In 1955, Carl Erik Josef Nyberg felt strongly enough about his innovative compressed air coupling that he started his own company to manufacture it. Using his initials as the company's name, Carl launched operations for CEJN in Skövde, Sweden, where the international headquarters have remained. Today you'll find CEJN manufacturing and sales operations on four continents in over 20 countries.

An extensive range of standard products for reliable service and flawless functions

Industry's strong acceptance of CEJN quick couplings around the world has made them the quality products of choice when customers need fluid systems to function without failure.

The standard product range includes quick coupling styles for applications involving the transfer of compressed air, hydraulic oils, fluids, gases, and other media. Also included in the CEJN product line are accessory products, such as adapters, fittings, hose, hose reels, air-preparation units, and blowguns.

Overall commitment to manufacture new products in line with market demands and customer requests

Using only high-quality raw material and state-of-the-art manufacturing and test equipment, CEJN operations in Skövde, Sweden, produce quick couplings that are synonymous with high quality, added value, and defect-free performance.

The company's hard-working commitment to developing new products also includes:

– Modifying existing products when higher performance standards are required – and “off-the-shelf” components won't do. By continually investing in new processes and

technologies, CEJN has the capability to modify products that exceed their original performance parameters and customer expectations.

– Designing and manufacturing limited quantities of custom couplings that are needed by customers to replace troublesome products or build into new or existing applications. CEJN provides complete product solutions from design to installation-ready components that are qualified, tested, and backed by after-sale support.

Whether it's a special coupling requirement for material construction, temperature range, end connection, or flow rate, CEJN engineers analyze each requirement and determine whether to build it into an existing product or an all-new design.

Bringing problem solving and economical quick connect solutions to customers

Economical benefits have been the guiding goal for all new developments at CEJN. Presenting customers with products that will not only outperform existing products or solve connection problems but also provide a good overall economy is always the goal.

Compressed air products with high-flow capacities and low pressure drops will need a lower energy input, providing good economical benefits. Hydraulic Plug-In products removes the need for tools and re-tightnings as well as minimizes service and maintenance times, again, providing good economical benefits. This is just a few examples of benefits provided with CEJN products and how CEJN works with a clear customer focus.

Quality Approach

– a part of a successful plan

Rigorous quality controls and in-house testing facilities prove valuable assets for quality minded customers.

Working with a quality system is a matter of course for CEJN. The company headquarters in Skövde, Sweden has been certified in accordance with ISO 9001 quality system standards since 1995. The certification recognizes that the systems, processes, and written procedures in place for product development, design, manufacturing, assembly, marketing, and sales are accurate and consistent.

CEJN marketing and sales functions are managed in Europe, North and South America, Asia, Africa, and Australia by CEJN companies and by independent dealers. CEJN's quality system covers all aspects of our product range, including products made in-house as well as sourced components. The couplings and their component parts are checked at several stages during the production process – no matter where the components are manufactured.

In the case of new product developments, rigorous in-house testing and testing in the field are carried out to ensure both functionality and quality before new products are released to the market. The majority of CEJN couplings are designed with a safety factor of 4:1 for minimum burst pressure to operating pressure. In addition, a number of functional tests, including connect/disconnect, pressure, and quality inspections, are performed before CEJN products are labeled, packaged and shipped to customer locations.



CEJN Corporate Headquarter
CEJN AB
Skövde, Sweden

CEJN Sales Offices:
CEJN Norden AB
Skövde, Sweden

CEJN Denmark Aps
Esbjerg, Denmark

CEJN Product GmbH
Troisdorf, Germany

CEJN France S.A.S
Paris, France

CEJN AG
Cham, Switzerland

CEJN Italy S.R.L.
Milan, Italy

CEJN Ibérica S.L.
Barcelona, Spain

CEJN Industrial Corporation
Chicago, USA

CEJN Do Brasil LTDA
Curitiba, Brazil

CEJN Australia PTY Limited
Sydney, Australia

CEJN Japan Corporation
Tokyo, Japan

CEJN Products Far East PTE LTD.
Singapore City, Singapore

CEJN Products Far East CO, LTD.
Seoul, Korea

CEJN Shanghai Fluid Systems CO
LTD
Shanghai, China


CEJN India Pvt. Ltd.
Bangalore, India



ISO 9001 certified since 1995.
ISO 14001 certified since 2006.



Quick Connect Couplings



Flow capacity measured at inlet pressure
6 bar (87 PSI), pressure drop 0.5 bar (7 PSI)

Series 220 – CEJN Original Standard



Nominal flow dia.: 5 mm (3/16")
Flow capacity: 580 l/min. (20.5 CFM)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread,
hose connection
Coupling: Nickel-plated brass
Nipple: Hardened zinc-plated steel

Features and other versions:

- One-hand operated
- High-flow capacity
- Small external dimensions
- Brass nipples available, series 221
- Valved nipple available, series 225



Series 141 – CEJN Original Miniature Standard



Nominal flow dia.: 2.5 mm (3/32")
Flow capacity: 86 l/min. (3.0 CFM)
Max. working pressure: 10 bar (145 PSI)
Connections: Female/male thread,
hose connection
Coupling: Chrome-plated brass
Nipple: Chrome-plated brass

Features and other versions:

- One-hand operated
- Extremely small external dimensions



Series 300 – (ARO 210)



Nominal flow dia.: 5.5 mm (7/32")
Flow capacity: 1050 l/min. (37.1 CFM)
Max. working pressure: 16 bar (230 PSI)
Connections: Female/male thread, hose connection
Stream-Line
Coupling: Zinc-plated steel/brass
Nipple: Hardened zinc-plated steel

Features and other versions:

- One-hand operated
- High-flow capacity
- Large range of connections
- Anti-hose whip nipples available
- Small external dimensions
- Pre-applied thread sealant
- Low connection force
- Available in Soft-Line version



Series 300 – Vented



Nominal flow dia.: 5.5 mm (7/32")
Flow capacity: 975 l/min. (34.4 CFM)
Max. working pressure: 12 bar (174 PSI)
Connections: Female/male thread,
hose connection, Stream-Line
Coupling: Zinc-plated steel/brass
Nipple: (see Series 300)

Features and other versions:

- Full automatic operation
- Low connection force
- Low noise level during disconnection
- Complies with standards;
ISO 4414 and EN 983
- Available in Soft-Line version
- Connects with nipple series 300



Series 303



Nominal flow dia.: 6.5 mm (1/4")
Flow capacity: 1450 l/min. (51.2 CFM)
Max. working pressure: 16 bar (232 PSI)
Connections: Female/male thread,
hose connection, Stream-Line
Coupling: Zinc-plated steel/brass
Nipple: Hardened zinc-plated steel

Features and other versions:

- One-hand operated
- Pre-applied thread sealant
- High-flow capacity
- Large range of connections
- Anti-hose whip nipples available
- Low connection force



Series 310 – (A-A 59439, ISO 6150 B)



Nominal flow dia.: 5.3 mm (7/32")
Flow capacity: 925 l/min. (32.7 CFM)
Max. working pressure: 16 bar (232 PSI)
Connections: Female/male thread, hose connection
Stream-Line, CEJN-Lock
Coupling: Zinc-plated steel/brass
Nipple: Hardened zinc-plated steel

Features and other versions:

- One-hand operated
- High-flow capacity
- Large range of connections
- Anti-hose whip nipples available
- Small external dimensions
- Pre-applied thread sealant
- Low connection force
- Available in Soft-Line version



Series 310 – Vented



Nominal flow dia.: 5.3 mm (7/32")
Flow capacity: 900 l/min. (31.8 CFM)
Max. working pressure: 12 bar (174 PSI)
Connections: Female/male thread, hose connection,
Stream-Line
Coupling: Zinc-plated steel/brass
Nipple: (see Series 310)

Features and other versions:

- Full automatic operation
- Low connection force
- Low noise level during disconnection
- Complies with standards;
ISO 4414 and EN 983
- Available in Soft-Line version
- Connects with nipple series 310




Coupling with valve:

Nipple with valve:

Coupling without valve:

Nipple without valve:



Series 315 — (Asian Standard)



Nominal flow dia.: 7.5 mm (5/16")
Flow capacity: 1950 l/min. (68.9 CFM)
Max. working pressure: 16 bar (232 PSI)
Connections: Female/male thread,
hose connection, Stream-Line
Coupling: Zinc-plated steel/brass
Nipple: Hardened zinc-plated steel

Features and other versions:

- One-hand operated
- High-flow capacity
- Large range of connections
- Anti-hose whip nipples available
- Pre-applied thread sealant
- Low connection force



Series 320 – CEJN Original Standard (Eurostandard 7.6 (7.4))



Nominal flow dia.: 7.6 mm (5/16")
Flow capacity: 2100 l/min. (74.2 CFM)
Max. working pressure: 16 bar (232 PSI)
Connections: Female/male thread, hose connection,
Stream-Line, CEJN-Lock
Coupling: Zinc-plated steel/brass
Nipple: Hardened zinc-plated steel

Features and other versions:

- One-hand operated
- Extremely high-flow capacity
- Large range of connections
- Anti-hose whip nipples
- All brass version available, series 321
- Pre-applied thread sealant
- Low connection force
- Available in Soft-Line version



Series 320 – Vented



Nominal flow dia.: 7.6 mm (5/16")
Flow capacity: 1900 l/min. (67.1 CFM)
Max. working pressure: 12 bar (174 PSI)
Connections: Female/male thread,
hose connection, Stream-Line
Coupling: Zinc-plated steel/brass
Nipple: (see Series 320 Standard)

Features and other versions:

- Full automatic operation
- Low connection force
- Low noise level during disconnection
- Complies with standards;
ISO 4414 and EN 983
- Available in Soft-Line version
- Connects with nipple series 320



Series 320 Aluminum – CEJN Original Standard



Nominal flow dia.: 7.6 mm (5/16")
Flow capacity: 2100 l/min. (74.2 CFM)
Max. working pressure: 16 bar (232 PSI)
Connections: Female thread,
hose connection, Stream-Line
Coupling: Aluminum
Nipple: (see Series 320 Standard)

Features and other versions:

- **Ultra light**
- Extra lightweight, weighs 50% less than standard 320
- One-hand operated
- Extremely high-flow capacity
- Pre-applied thread sealant
- Low connection force
- Connects with nipple series 320 standard



Series 342 – CEJN Original Standard



Nominal flow dia.: 7.4 mm (9/32")
Flow capacity: 1950 l/min. (68.9 CFM)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread,
hose connection, Stream-Line
Coupling: Zinc-plated steel/brass
Nipple: Hardened zinc-plated steel

Features and other versions:

- One-hand operated to connect
- Automatic safety locking feature
- Large range of connections
- Anti-hose whip nipples available



Series 408



Nominal flow dia.: 9.5 mm (3/8")
Flow capacity: 3450 l/min. (121.8 CFM)
Max. working pressure: 16 bar (232 PSI)
Connections: Female/male thread,
hose connection, Stream-Line
Coupling: Zinc-plated steel/brass
Nipple: Hardened zinc-plated steel

Features and other versions:

- One-hand operated
- Extremely high-flow capacity
- Large range of connections
- Anti-hose whip nipples available
- Low connection force



Series 410 – CEJN Original Standard (Eurostandard 10.4)



Nominal flow dia.: 10.4 mm (13/32")
Flow capacity: 3900 l/min. (137.7 CFM)
Max. working pressure: 16 bar (232 PSI)
Connections: Female/male thread,
hose connection, Stream-Line
Coupling: Zinc-plated steel/brass
Nipple: Hardened zinc-plated steel

Features and other versions:

- One-hand operated
- Extremely high-flow capacity
- Large range of connections
- Anti-hose whip nipples available
- All brass version available, series 411
- Low connection force



Series 410 – Vented



Nominal flow dia.: 10.4 mm (13/32")
Flow capacity: 3700 l/min. (130.7 CFM)
Max. working pressure: 16 bar (232 PSI)
Connections: Female/male thread,
hose connection, Stream-Line
Coupling: Zinc-plated steel/brass
Nipple: (see Series 410)

Features and other versions:

- Full automatic operation
- Low connection force
- Low noise level during disconnection
- Complies with standards;
ISO 4414 and EN 983
- Connects with nipple series 410



Coupling with valve:



Nipple with valve:



Coupling without valve:



Nipple without valve:



Series 430 – (A-A 59439, ISO 6150 B)



Nominal flow dia.: 8.2 mm (5/16")
Flow capacity: 2350 l/min. (83.0 CFM)
Max. working pressure: 16 bar (232 PSI)
Connections: Female/male thread,
hose connection, Stream-Line
Coupling: Zinc-plated steel/brass
Nipple: Hardened zinc-plated steel

Features and other versions:

- One-hand operated
- High-flow capacity
- Large range of connections
- Anti-hose whip nipples available
- Low connection force



Series 442 – CEJN Original Standard



Nominal flow dia.: 10.4 mm (13/32")
Flow capacity: 3950 l/min. (139.5 CFM)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread,
hose connection
Coupling: Zinc-plated steel/brass
Nipple: Hardened zinc-plated steel

Features and other versions:

- One-hand operated to connect
- Automatic safety locking feature
- Large range of connections
- Anti-hose whip nipples available



Series 550 – (A-A 59439, ISO 6150 B)



Nominal flow dia.: 11 mm (7/16")
Flow capacity: 3750 l/min. (132.4 CFM)
Max. working pressure: 16 bar (232 PSI)
Connections: Female/male thread,
hose connection
Coupling: Zinc-plated steel/brass
Nipple: Hardened zinc-plated steel

Features and other versions:

- One-hand operated
- Extremely high-flow capacity
- Large range of connections
- Anti-hose whip nipples available
- Vented version, series 555
- Extremely small external dimensions
- Low weight
- Low connection force



Series 550 – Vented




Nominal flow dia.: 11 mm (7/16")
Flow capacity: 3200 l/min. (113.0 CFM)
Max. working pressure: 16 bar (232 PSI)
Connections: Female/male thread,
hose connection
Coupling: Zinc-plated steel/brass
Nipple: (see Series 550)

Features and other versions:

- Full automatic operation
- High-flow capacity
- Large range of connections
- Complies with standards;
ISO 4414 and EN 983
- Connects with nipple series 550
- Extremely low connection force
- Low noise level during disconnection



Button Couplings



Series 291 – Vented, (ISO Standard 6150 C)



Nominal flow dia.: 5.5 mm (7/32")
Flow capacity: 640 l/min. (22.6 CFM)
Max. working pressure: 12 bar (174 PSI)
Connections: Female/male thread,
hose connection
Coupling: Steel
Nipple: Nickel-plated steel

Features and other versions:

- Large range of connections
- One-hand operated
- High-flow capacity



Series 381 – Vented, (ISO Standard 6150 C)



Nominal flow dia.: 8.0 mm (5/16")
Flow capacity: 1050 l/min. (37.1 CFM)
Max. working pressure: 10 bar (145 PSI)
Connections: Female/male thread,
hose connection
Coupling: Steel
Nipple: Nickel-plated steel

Features and other versions:

- Large range of connections
- One-hand operated
- High-flow capacity



Series 471 – Vented, (ISO Standard 6150 C)



Nominal flow dia.: 11 mm (7/16")
Flow capacity: 2350 l/min. (83.0 CFM)
Max. working pressure: 8 bar (116 PSI)
Connections: Female/male thread,
hose connection
Coupling: Steel
Nipple: Nickel-plated steel

Features and other versions:

- Large range of connections
- One-hand operated
- High-flow capacity



Coupling with valve:



Nipple with valve:



Coupling without valve:




Nipple without valve:





Blowguns



Airflow measured at inlet pressure 6 bar (87 PSI)

Series 208 – Blowgun

Airflow: 500 l/min (17.7 CFM)*
Max. working pressure: 16 bar (232 PSI)*
Connections: 1/4" Female thread
Weight: 112 g. (3.6 oz)*
Material: POM (body), brass (valve)

Features and other versions:


- Noise reduced version with Star-Tip tube available
- Safety gun with air regulator available
- Ergonomical design
- Insulated and hard-wearing
- Large range of nozzles and tubes available
- Complies with OSHA directives #100-1**
- Complies with EU machine directive §1.5.8**

* Version with 90 mm standard tube

** Applies to some versions



Hose



Straight Braided Hose

Size (IDxOD mm): 6.5x10, 8x12, 9.5x13.5, 11x16, 13x18
Max. working pressure: Up to 16 bar (232 PSI)
Material: Ester-based Polyurethane reinforced with polyester fibre

Features and other versions:

- Wide temperature range
- Light and flexible
- Very good rebound qualities
- Long life cycle with outstanding aging qualities
- Abrasion resistant
- High impact strength
- High tensile and tear strength
- Resistant to oils, solvents and other non-aqueous solutions



Straight Non-Braided Hose

Size (IDxOD mm): 6.5x10, 8x12, 9.5x13.5, 11x16
Max. working pressure: 10 bar (145 PSI)
Material: Ester-based Polyurethane

Features and other versions:

- Wide temperature range
- Light and flexible
- Very good rebound qualities
- Long life cycle with outstanding aging qualities
- Abrasion resistant
- High impact strength
- High tensile and tear strength
- Resistant to oils, solvents and other non-aqueous solutions



Straight Braided Electrically Conductive Hose

Size (IDxOD mm): 6.5x10, 8x12, 11x16
Max. working pressure: 16 bar (232 PSI)
Material: Ester-based Polyurethane reinforced with polyester fibre

Features and other versions:

- Wide temperature range
- Light and flexible
- Very good rebound qualities
- Long life cycle with outstanding aging qualities
- Abrasion resistant
- High impact strength
- High tensile and tear strength
- Resistant to oils, solvents and other non-aqueous solutions.
- Anti-static shield feature with an integral wire that dissipates electro-static discharges



Straight Braided Anti-Spark Hose

Size (IDxOD mm): 6.5x10, 8x12, 11x16
Max. working pressure: Up to 14 bar (203 PSI)
Material: Ester-based Polyurethane reinforced with polyester fibre

Features and other versions:

- Wide temperature range
- Light and flexible
- Very good rebound qualities
- Long life cycle with outstanding aging qualities
- Abrasion resistant
- High impact strength
- High tensile and tear strength
- Resistant to oils, solvents and other non-aqueous solutions
- Resistant to sparks and scorching



Straight Braided Hose for Water

Size (IDxOD mm): 8x12, 11x16
Max. working pressure: 10 bar (145 PSI)
Material: Ether-based Polyurethane reinforced with polyester fibre

Features and other versions:

- Wide temperature range
- Light and flexible
- Very good rebound qualities
- Long life cycle with outstanding aging qualities
- Abrasion resistant
- High impact strength
- High tensile and tear strength
- Resistant to oils, solvents and both non-aqueous and aqueous solutions



Coupling with valve: ➡



Nipple with valve: ➡



Coupling without valve: ➡



Nipple without valve: ➡



Spiral Non-Braided Hose

Size (IDxOD mm): 5x8, 6.5x10, 8x12, 11x16
Length: from 2.5 to 10 m (from 8 to 33 ft)
Max. working pressure: 10 bar (145 PSI)
Material: Ester-based Polyurethane

Features and other versions:

- Wide temperature range
- Light and flexible
- Excellent recoil qualities
- Long life cycle with outstanding aging qualities
- Abrasion resistant
- High impact strength
- High tensile and tear strength
- Resistant to oils, solvents and other non-aqueous solutions



Spiral Non-Braided Anti-Spark Hose

Size (IDxOD mm): 6.5x10, 8x12
Length: from 2.5 to 10 m (from 8 to 33 ft)
Max. working pressure: 10 bar (145 PSI)
Material: Ester-based Polyurethane

Features and other versions:

- Wide temperature range
- Light and flexible with very good rebound qualities
- Long life cycle with outstanding aging qualities
- High impact strength abrasion resistant
- High tensile and tear strength
- Resistant to oils, solvents and other non-aqueous solutions
- Resistant to sparks and scorching

APPROVED according to EN 12419:1999 and EN 1835:1999 for breathing air use, when used with approved breathing air filters and masks



PUR Hosekits


Size (IDxOD mm): 5x8, 6.5x10, 8x12, 11x16
Length: from 2 to 20 m (from 6.5 to 65.5 ft)
Max. working pressure: differs between sizes
Hose: Straight braided, Straight non-braided or Spiral
Connections: Series 300, 310, 320 or adapters

Features and other versions:

- Wide temperature range
- Light and flexible with very good rebound qualities
- Long life cycle with outstanding aging qualities
- Abrasion resistant
- High impact strength
- High tensile and tear strength
- Resistant to oils, solvents and other non-aqueous solutions
- Kits with accessories and blowguns available
- Wide range of hose and connection mixes available



Hose and Cable Reels




Hose Reels for Compressed Air

Hose dimension (mm): 6.5x10, 8x12, 9.5x13.5, 11x16
Hose: Braided PUR
Reel diameter: 330 mm, 430 mm
Hose length: from 7 to 16 m (from 23 to 52.5 ft)
Max. working pressure: Up to 16 bar (232 PSI)

Features and other versions:

- Available in several casing sizes, hose dimensions and lengths
- Enclosed housing for reel mechanism protection
- Specially prepared hose ensures flawless feeding action
- CE marked and complies with 89/392/EEC
- Continuous feeding action possible when disengaging stop function
- For ceiling or wall-mounting, swivels 300°
- Available with Anti-Spark hose (9.5x13.5 mm)



Hose Reels for Water

Hose dimension (mm): 9.5x13.5
Hose: Braided PUR
Reel diameter: 430 mm
Hose length: 14 m (46 ft)
Max. working pressure: 9 bar (130 PSI)

Features and other versions:

- Enclosed housing for reel mechanism protection
- Specially prepared hose ensures flawless feeding action
- CE marked and complies with 89/392/EEC
- For ceiling or wall-mounting, swivels 300°



Cable Reels


Cable: PVC
Reel diameter: 330 mm, 430 mm
Cable length: 10 and 17 m (33 and 56 ft)
Current: 10 and 16 ampere
Voltage: 230 V
Connections: Schuko and CH plug
Power output: 1000 W (fully wound), 3500 W (fully unwound)

Features and other versions:

- Enclosed housing for reel mechanism protection
- CE marked and complies with 89/392/EEC
- Approved by TÜV (versions with CH plugs also approved by SEV)
- Continuous feeding action possible when disengaging stop function
- For ceiling or wall-mounting, swivels 300°



Accessories



Coupling with valve:



Nipple with valve:




Coupling without valve:



Nipple without valve:





Adapters

Max. working pressure: 35 bar (508 PSI)
Material: Plated brass

Features and other versions:

- Wide range of connections
- Plated for better protection against corrosion



Series 900 – Soft-Line

Material: Chloroprene

Features and other versions:

- Available as accessories for standard coupling series that doesn't feature integrated soft-line versions
- Available for series 303, 310, 315, 320
- Non-abrasive to surrounding components
- Ideal for work on delicate surfaces
- Easy to install
- Delivered with assembly tool
- Wide temperature range



Series 902 – Multi-Link

Max. working pressure: 10 bar (145 PSI)
Material: Nickel-plated brass

Features and other versions:

- Up to six sections can be connected
- Simple assembly
- Stop valve available for the use of two media in the same unit
- Available with integral quick-couplings series 300, 305, 310, 315 and 320
- Also available with female thread adapter



Series 903 – FRL

– Filters – Regulators – Lubricators
– Filterregulators – Combined systems
Max. working pressure: 16 bar (130 PSI)

Features and other versions:

- 4 body sizes
- High flow rates
- Hard-wearing materials
- Filtration capacity down to 0.01 µm
- Regulating pressures between 0.5 and 12 bar (7 and 174 PSI)
- Rolling diaphragm for precision regulation and low hysteresis, less than 0.2 bar (3 PSI)
- Selective oil fog lubrication
- Several system combinations available



Air Treatment Components


Series 903 – FRL

CEJN FRL products are designed to provide constant high-quality air within compressed air systems. High-quality air achieved by FRL components results in important benefits to tools and machines, including decreased downtime, minimized wear and tear, and increased lifespan.

FRLs – often called air-preparation devices – have important functions in the compression cycle. When installed correctly, they ensure smooth, economical operation without interruption and a reliable energy source.


CEJN offers filter, regulator, and lubricator products as stand-alone components or in complete system packages.

From FRL units to compressed air couplings, CEJN offers all the necessary components to ensure reliable compressed air performance worldwide.





Quick Connect Couplings




Series 171 – CEJN Original Standard



Nominal flow dia.: 5 mm (3/16")
 Max. working pressure: 10 bar (145 PSI)
 Connections: Female, hose connection
 Coupling: Yellow pickled brass, aluminum
 Nipple: Yellow pickled brass, aluminum

- Features and other versions:**
- Automatic safety locking device
 - Double seal function for extra safety
 - Available with left- or right hand threads
 - Cross connection between series impossible
 - Color-coded acc. to international standards
 - Series 171 red – acetylene



Series 172 – CEJN Original Standard



Nominal flow dia.: 5 mm (3/16")
 Max. working pressure: 10 bar (145 PSI)
 Connections: Female, hose connection
 Coupling: Yellow pickled brass, aluminum
 Nipple: Yellow pickled brass, aluminum

- Features and other versions:**
- Automatic safety locking device
 - Double seal function for extra safety
 - Cross connection between series impossible
 - Color-coded acc. to international standards
 - Series 172 orange – LP-gas



Series 181 – CEJN Original Standard



Nominal flow dia.: 5 mm (3/16")
 Max. working pressure: 10 bar (145 PSI)
 Connections: Female, hose connection
 Coupling: Yellow pickled brass, aluminum
 Nipple: Yellow pickled brass, aluminum

- Features and other versions:**
- Automatic safety locking device
 - Double seal function for extra safety
 - Cross connection between series impossible
 - Color-coded acc. to international standards
 - Series 181 blue – oxygen gas



Gas Collection

Series 171, 172 and 181

Quick couplings for gas is the smallest product area for CEJN, but is by no means less important than any other. CEJN's gas range was first introduced in the late 70's after a customer request for couplings for welding equipment.

The product range feature automatic safety locking, double seal functions for extra safety and color-coding on both coupling and nipple. Vitally important is also the non-interchangeability feature preventing unintentional connection between different gas lines, preventing, potentially, dangerous compounds from mixing.




All CEJN products for gas applications are made in brass to prevent hazardous sparks. With gas applications safety always comes first, no shortcuts are allowed. CEJN's normally very stringent tests during assembly and before shipment are extra valuable for this segment.

Made in brass and aluminum with nitrile or EPDM seals, the couplings are suited for most gas applications and environments, such as welding equipment both indoors and outdoors, gas burners and hot air balloons. The main markets for our range is Scandinavia and Germany even though the products are sold throughout the CEJN group worldwide.



Quick Connect Couplings



Flow capacity measured at inlet pressure
6 bar (87 PSI), pressure drop 0.5 bar (7 PSI)

Series 141 – CEJN Original Miniature Standard



Nominal flow dia.: 2.5 mm (3/32")
Flow capacity: 86 l/min. (3.0 CFM)
Max. working pressure: 10 bar (145 PSI)
Connections: Female/male thread,
hose connection
Coupling: Chrome-plated brass
Nipple: Chrome-plated brass

Features and other versions:

- One-hand operated
- Extremely small external dimensions
- Suitable for supply of liquids in closed units



Series 221 – CEJN Original Standard



Nominal flow dia.: 5 mm (3/16")
Flow capacity: 580 l/min. (20.5 CFM)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread,
hose connection
Coupling: Chrome-plated brass
Nipple: Chrome-plated brass

Features and other versions:

- One-hand operated
- High flow capacity
- Small external dimensions
- Double shut-off version, series 225



Series 341 – CEJN Original Standard



Nominal flow dia.: 7.4 mm (9/32")
Flow capacity: 1950 l/min. (69 CFM)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread,
hose connection
Coupling: Nickel-plated brass
Nipple: Nickel-plated brass

Features and other versions:

- One-hand operated to connect
- Automatic safety locking feature
- Large range of connections available
- Extremely high flow capacity



Series 342 – CEJN Original Standard



Nominal flow dia.: 7.4 mm (9/32")
Flow capacity: 1950 l/min. (69 CFM)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread,
hose connection, Stream-Line
Coupling: Nickel-plated brass/steel
Nipple: Hardened zinc-plated steel

Features and other versions:

- One-hand operated to connect
- Extremely high flow capacity
- Automatic safety locking feature
- Large range of connections available



Series 344 – CEJN Original Standard



Nominal flow dia.: 7.4 mm (9/32")
Flow capacity: 1950 l/min. (69 CFM)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread,
hose connection
Coupling: Nickel-plated brass
Nipple: Nickel-plated brass

Features and other versions:

- One-hand operated to connect
- Automatic safety locking feature
- Large range of connections available
- Extremely high flow capacity
- Light weight
- Stainless steel nipples available



Series 345 – CEJN Original Standard



Nominal flow dia.: 6.2 mm (1/4")
Flow capacity: 1100 l/min. (39 CFM)
Max. working pressure: 35 bar (500 PSI)
Connections: Female/male thread,
hose connection
Coupling: Nickel-plated brass
Nipple: Nickel-plated brass

Features and other versions:

- One-hand operated to connect
- Automatic safety locking feature
- Large range of connections available
- Extremely high flow capacity



Series 346 – CEJN Original Standard



Nominal flow dia.: 7.4 mm (9/32")
Flow capacity: 800 l/min. (28 CFM)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread,
hose connection
Coupling: Stainless steel
Nipple: Stainless steel

Features and other versions:

- One-hand operated to connect
- Automatic safety locking feature
- Large range of connections available
- Extremely high flow capacity



Coupling with valve:

Nipple with valve:

Coupling without valve:

Nipple without valve:

Series 347 – CEJN Original Standard



Nominal flow dia.: 6.2 mm (1/4")
Flow capacity: 1100 l/min. (39 CFM)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread,
hose connection, Stream-Line
Coupling: Nickel-plated brass
Nipple: Nickel-plated brass

Features and other versions:

- One-hand operated to connect
- High flow capacity
- Automatic safety locking feature



Series 348



Nominal flow dia.: 4.1 mm (5/32")
Flow capacity: 650 l/min. (23 CFM)
Max. working pressure: 10 bar (145 PSI)
Connections: Hose connection
Coupling: Nickel-plated brass/stainless steel
Nipple: Stainless steel body/nickel-plated brass

Features and other versions:

- One-hand operated to connect
- Stainless steel valve opener
- Automatic safety locking feature



Series 441 – CEJN Original Standard



Nominal flow dia.: 10.4 mm (13/32")
Flow capacity: 3950 l/min. (140 CFM)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread,
hose connection
Coupling: Nickel-plated brass
Nipple: Nickel-plated brass

Features and other versions:

- One-hand operated to connect
- High flow capacity
- Automatic safety locking feature



Series 442 – CEJN Original Standard



Nominal flow dia.: 10.4 mm (13/32")
Flow capacity: 3950 l/min. (140 CFM)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread,
hose connection
Coupling: Nickel-plated brass/steel
Nipple: Hardened zinc-plated steel

Features and other versions:

- One-hand operated
- High flow capacity
- Automatic safety locking feature



Hose



Spiral Non-Braided Anti-Spark Hose




Size (IDxOD mm): 6.5x10, 8x12
Length: from 2.5 to 10 m (from 8 to 33 ft)
Max. working pressure: 10 bar (145 PSI)
Material: Ester-based Polyurethane

Features and other versions:

- Wide temperature range
- Light and flexible with very good rebound qualities
- Long life cycle with outstanding aging qualities
- High impact strength abrasion resistant
- High tensile and tear strength
- Resistant to oils, solvents and other non-aqueous solutions
- Resistant to sparks and scorching

! APPROVED according to EN 12419:1999 and EN 1835:1999 for breathing air use, when used with approved breathing air filters and masks



Coupling with valve:



Nipple with valve:



Coupling without valve:



Nipple without valve:



Breathing Air

Series 347 Collection

CEJN Series 347 features a double shut-off valve and will not interchange with any other CEJN coupling. This feature is critical especially in manufacturing environments where compressed air lines and breathing air lines must not be crossconnected. The locking sleeve of Series 347 couplings is coded with a green marking that indicates to users that the couplings are non-compatible with other series.


Series 347 have a working pressure of 35 bar (508 PSI) and offer many of the design features of CEJN's range of breathing air couplings. These features include a high-flow capacity valve, an integrated safety mechanism that prevents unintentional disconnection, and an easy-to-grip locking sleeve.

In addition to manufacturing environments, Series 347 couplings are also ideal for applications that require a closed system in disconnected mode, such as diving equipment that utilizes surface air.





Quick Connect Couplings



Flow capacity measured at 4 bar (58 PSI) pressure drop

Series 141 – CEJN Original Miniature Standard




Nominal flow dia.: 2.5 mm (3/32")
Flow capacity: 3.5 l/min (0.77 GPM uk)
Max. working pressure: 10 bar (145 PSI)
Connections: Female/male thread, hose connection
Coupling: Chrome-plated brass
Nipple: Chrome-plated brass

Features and other versions:

- One-hand operated
- Extremely small external dimensions



Series 220/221 – CEJN Original Standard



Nominal flow dia.: 5 mm (3/16")
Flow capacity: 26 l/min (5.72 GPM uk)
Max. working pressure: 35 bar (500 PSI)
Connections: Female/male thread, hose connection
Coupling: Nickel-plated brass
Nipple: Chrome-plated brass

Features and other versions:

- One-hand operated
- High-flow capacity
- Small external dimensions
- Steel nipple, series 220
- Brass nipple, series 221
- Double shut-off version, series 225
- Valveless couplings available on request



Series 225




Nominal flow dia.: 3 mm (1/8")
Flow capacity: 8 l/min (1.76 GPM)
Max. working pressure: 35 bar (500 PSI)
Connections: Female thread
Coupling: Chrome-plated brass
Nipple: Chrome-plated brass

Features and other versions:

- One-hand operation
- High-flow capacity
- Small external dimensions
- Double shut-off version



Series 267 – Non-Drip




Nominal flow dia.: 4 mm (5/32")
Flow capacity: 17 l/min (3.7 GPM uk)
Max. working pressure: 20 bar (290 PSI)
Connections: Female thread
Coupling: Nickel-plated brass
Nipple: Nickel-plated brass

Features and other versions:

- Couplings and nipples available in both valved and valvless styles
- Non-spillage design
- Optional safety features available
- Dust caps available
- Stainless steel version, series 277



Series 277 – Non-Drip



Nominal flow dia.: 4 mm (5/32")
Flow capacity: 17 l/min (3.7 GPM uk)
Max. working pressure: 20 bar (290 PSI)
Connections: Female thread
Coupling: Stainless steel AISI 316
Nipple: Stainless steel AISI 316

Features and other versions:

- Couplings and nipples available in both valved and valvless styles
- Non-spillage design
- Optional safety features available
- Dust caps available
- Nickel plated brass version, series 267



Series 321 – CEJN Original Standard



Nominal flow dia.: 7.4 mm (9/32")
Flow capacity: 78 l/min (17.1 GPM uk)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread, hose connection, Stream-Line
Coupling: Nickel-plated brass
Nipple: Nickel-plated brass

Features and other versions:

- One-hand operated
- Extremely high-flow capacity
- Large range of connections



Series 322 – CEJN Original Standard




Nominal flow dia.: 7.4 mm (9/32")
Flow capacity: 90 l/min (19.8 GPM uk)
Max. working pressure: 200 bar (2900 PSI)
Connections: Female/male thread
Coupling: Nickel-plated brass/steel
Nipple: Hardened steel, yellow zinc-plated

Features and other versions:


- One-hand operated
- High burst/working pressure
- Extremely high-flow capacity
- Nipples, chemically nickel-plated steel available on request



Coupling with valve: 

Nipple with valve: 

Coupling without valve: 

Nipple without valve: 

Series 324 – CEJN Original Standard




Nominal flow dia.: 6.2 mm (1/4")
Flow capacity: 42 l/min. (9.2 GPM uk)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread, hose connection
Coupling: Nickel-plated brass
Nipple: Nickel-plated brass

Features and other versions:

- One-hand operated
- Double shut-off version
- Small external dimensions
- Dust caps included as standard
- Stainless steel version, series 326
- Couplings also connects with valveless nipple series 321



Series 326 – CEJN Original Standard



Nominal flow dia.: 6.2 mm (1/4")
Flow capacity: 28 l/min. (6.2 GPM uk)
Max. working pressure: 70 bar (1015 PSI)
Connections: Female/male thread
Coupling: Stainless steel AISI 316
Nipple: Stainless steel AISI 316

Features and other versions:

- One-hand operated
- Small external dimensions
- Dust caps included as standard
- All brass version, series 324
- Nipples with or without valve available



Series 411 – CEJN Original Standard



Nominal flow dia.: 10.4 mm (13/32")
Flow capacity: 156 l/min. (34.3 GPM uk)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread, hose connection
Coupling: Nickel-plated brass
Nipple: Chrome-plated brass

Features and other versions:

- One-hand operated
- Extremely high-flow capacity
- Large range of connections



Series 412 – CEJN Original Standard



Nominal flow dia.: 10.4 mm (13/32")
Flow capacity: 167 l/min. (36.7 GPM uk)
Max. working pressure: 200 bar (2900 PSI)
Connections: Female/male thread
Coupling: Nickel-plated steel/brass
Nipple: Hardened steel, zinc-plated

Features and other versions:

- One-hand operated
- Extremely high-flow capacity
- Nipples, chemically nickel-plated steel available on request
- Valveless nipples available



Series 414 – CEJN Original Standard




Nominal flow dia.: 8.9 mm (11/32")
Flow capacity: 71 l/min. (15.6 GPM uk)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread, hose connection
Coupling: Chrome-plated brass
Nipple: Chrome-plated brass

Features and other versions:

- One-hand operated
- Double shut-off version
- High-flow capacity
- Small external dimensions
- Dust caps included as standard
- Large range of connections
- Stainless steel version, series 416
- Coupling also connects with valveless nipples series 411



Series 416 – CEJN Original Standard



Nominal flow dia.: 8.9 mm (11/32")
Flow capacity: 85 l/min. (18.7 GPM uk)
Max. working pressure: 35 bar (508 PSI)
Connections: Female/male thread
Coupling: Stainless steel AISI 316
Nipple: Stainless steel AISI 316

Features and other versions:

- One-hand operated
- High-flow capacity
- Small external dimensions
- Dust caps included as standard
- Large range of connections available
- All brass version, series 414



Series 417 – CEJN Original Standard



Nominal flow dia.: 10.5 mm (13/32")
Flow capacity: 226 l/min. (49.7 GPM uk)
Max. working pressure: 20 bar (290 PSI)
Connections: Female/male thread, hose connection
Coupling: Chrome-plated brass
Nipple: (see Series 411)

Features and other versions:

- Adapted to home and garden use
- Straight-through version
- High-flow capacity
- Large range of connections
- Connects with nipple series 411



Series 467 – Non-Drip



Nominal flow dia.: 6 mm (1/4")
Flow capacity: 36 l/min. (7.9 GPM uk)
Max. working pressure: 20 bar (290 PSI)
Connections: Female thread
Coupling: Nickel-plated brass
Nipple: Nickel-plated brass

Features and other versions:

- Couplings and nipples available in both valved and valveless styles
- Non-spillage design
- Optional safety features available
- Dust caps available
- Stainless steel version, series 477



Coupling with valve:



Nipple with valve:



Coupling without valve:




Nipple without valve:





Series 477 – Non-Drip




Nominal flow dia.: 6 mm (1/4")
Flow capacity: 36 l/min (7.9 GPM uk)
Max. working pressure: 20 bar (290 PSI)
Connections: Female thread
Coupling: Stainless steel AISI 316
Nipple: Stainless steel AISI 316

Features and other versions:

- Couplings and nipples available in both valved and valvless styles
- Non-spillage design
- Optional safety features available
- Dust caps available
- Nickel plated brass version, series 467



Series 567 – Non-Drip




Nominal flow dia.: 9 mm (11/32")
Flow capacity: 76 l/min (16.7 GPM uk)
Max. working pressure: 20 bar (290 PSI)
Connections: Female thread
Coupling: Nickel-plated brass
Nipple: Nickel-plated brass

Features and other versions:

- Couplings and nipples available in both valved and valvless styles
- Non-spillage design
- Optional safety features available
- Dust caps available
- Stainless steel version, series 577



Series 577 – Non-Drip



Nominal flow dia.: 9 mm (11/32")
Flow capacity: 76 l/min (16.7 GPM uk)
Max. working pressure: 20 bar (290 PSI)
Connections: Female thread
Coupling: Stainless steel AISI 316
Nipple: Stainless steel AISI 316

Features and other versions:

- Couplings and nipples available in both valved and valvless styles
- Non-spillage design
- Optional safety features available
- Dust caps available
- Nickel plated brass version, series 567



Series 604 – CEJN Original Standard



Nominal flow dia.: 14.5 mm (9/16")
Flow capacity: 210 l/min. (46.2 GPM uk)
Max. working pressure: 35 bar (508 PSI)
Connections: Female thread
Coupling: Chrome-plated brass
Nipple: Chrome-plate brass

Features and other versions:

- One-hand operated
- Easy connection
- High-flow capacity
- Dust caps included as standard
- Nipples available with or without valve
- Stainless steel version, series 606



Series 606 – CEJN Original Standard




Nominal flow dia.: 14.5 mm (9/16")
Flow capacity: 207 l/min. (45.5 GPM uk)
Max. working pressure: 35 bar (508 PSI)
Connections: Female thread
Coupling: Stainless steel AISI 316
Nipple: Stainless steel AISI 316

Features and other versions:

- One-hand operated
- Easy connection
- High-flow capacity
- Dust caps included as standard
- Nipples available with or without valve
- All brass version, series 604



Series 667 – Non-Drip




Nominal flow dia.: 14 mm (9/16")
Flow capacity: 168 l/min (37.0 GPM uk)
Max. working pressure: 20 bar (290 PSI)
Connections: Female thread
Coupling: Nickel-plated brass
Nipple: Nickel-plated brass

Features and other versions:

- Couplings and nipples available in both valved and valvless styles
- Non-spillage design
- Optional safety features available
- Dust caps available
- Stainless steel version, series 677



Series 677 – Non-Drip




Nominal flow dia.: 14 mm (9/16")
Flow capacity: 168 l/min (37.0 GPM uk)
Max. working pressure: 20 bar (290 PSI)
Connections: Female thread
Coupling: Stainless steel AISI 316
Nipple: Stainless steel AISI 316

Features and other versions:

- Couplings and nipples available in both valved and valvless styles
- Non-spillage design
- Optional safety features available
- Dust caps available
- Nickel plated brass version, series 667



Series 704 – CEJN Original Standard



Nominal flow dia.: 19 mm (3/4")
Flow capacity: 271 l/min (59.6 GPM uk)
Max. working pressure: 35 bar (508 PSI)
Connections: Female thread
Coupling: Chrome-plated brass
Nipple: Chrome-plated brass

Features and other versions:

- One-hand operated
- Easy connection
- High-flow capacity
- Dust caps included as standard
- Nipples available with or without valve
- Stainless steel version, series 706



Coupling with valve:



Nipple with valve:



Coupling without valve:



Nipple without valve:



Series 706 – CEJN Original Standard




Nominal flow dia.: 19 mm (3/4")
Flow capacity: 227 l/min (49.9 GPM uk)
Max. working pressure: 35 bar (508 PSI)
Connections: Female thread
Coupling: Stainless steel AISI 316
Nipple: Stainless steel AISI 316

Features and other versions:

- One-hand operated
- Easy connection
- High-flow capacity
- Dust caps included as standard
- Nipples available with or without valve
- All brass version, series 704



Series 767 – Non-Drip




Nominal flow dia.: 19 mm (3/4")
Flow capacity: 306 l/min (67.3 GPM uk)
Max. working pressure: 20 bar (290 PSI)
Connections: Female thread
Coupling: Nickel-plated brass
Nipple: Nickel-plated brass

Features and other versions:

- Couplings and nipples available in both valved and valvless styles
- Non-spillage design
- Optional safety features available
- Dust caps available
- Stainless steel version, series 777



Series 777 – Non-Drip




Nominal flow dia.: 19 mm (3/4")
Flow capacity: 306 l/min (67.3 GPM uk)
Max. working pressure: 20 bar (290 PSI)
Connections: Female thread
Coupling: Stainless steel AISI 316
Nipple: Stainless steel AISI 316

Features and other versions:

- Couplings and nipples available in both valved and valvless styles
- Non-spillage design
- Optional safety features available
- Dust caps available
- Nickel plated brass version, series 767



Hose and Hose Reels




Hose Reels for Water

Hose dimension (IDxOD mm): 9.5x13.5
Hose: Braided PUR
Reel diameter: 430 mm
Hose length: 14 m (46 ft)
Max. working pressure: 9 bar (130 PSI)

Features and other versions:

- Enclosed housing for reel mechanism protection
- Specially prepared hose ensures flawless feeding action
- CE marked and complies with 89/392/EEC
- For ceiling or wall-mounting, swivels 300°



Straight Braided Hose for Water

Size (IDxOD mm): 8x12, 11x16
Max. working pressure: 10 bar (145 PSI)
Material: Ether-based Polyurethane reinforced with polyester fibre

Features and other versions:

- Wide temperature range
- Light and flexible
- Very good rebound qualities
- Long life cycle with outstanding aging qualities
- Abrasion resistant
- High impact strength
- High tensile and tear strength
- Resistant to oils, solvents and both non-aqueous and aqueous solutions



Non-Drip

Fluid Couplings Range

CEJN Non Drip couplings are solely designed for low-pressure fluid and vacuum applications. The products are suitable for all types of fluid lines, even those as diverse as beverages, salt water and oil.

The range has two important design features:

- A modular construction, all coupling and nipple components have standardized dimensions making them interchangeable, which results in practically unlimited combination possibilities.
- A non-drip design, which ensures virtually zero spillage and eliminates pollution and air inclusion during connection and disconnection.



The products are available in two different materials, nickel-plated brass and stainless steel AISI 316, and offered with four different seals: nitrile, Viton®, EPDM and Kalrez®.

Coupling with valve:



Nipple with valve:



Coupling without valve:




Nipple without valve:





Quick Connect Couplings



Flow capacity measured at pressure drop 0.4 MPa
(0.1 MPa for the X65 series)

Series 325 – CEJN Original Standard



Nominal flow dia.: 6.2 mm (1/4")
Flow capacity: 33 l/min. (7.3 GPM uk)
Max. working pressure: 25 MPa
Connections: Female thread
Coupling: Chrome-plated steel
Nipple: Hardened steel (zink chromate plating)

Features and other versions:

- One-hand operated
- Small external dimensions
- Dust caps included as standard
- All brass version, series 324
- Stainless steel version, series 326



Series 365 – Flat-Face (ISO 16028)



Nominal flow dia.: 10.0 mm (3/8")
Flow capacity: 23 l/min. (5.1 GPM uk)
Max. working pressure: 25 MPa
Connections: Female thread
Coupling: Steel (yellow zinc chromate plating)
Nipple: Hardened steel (yellow zinc chromate plating)

Features and other versions:

- Flat-face design to minimize spillage
- One-hand operated
- Extra security locking feature prevents unintentional disconnection
- Couplings feature hardened locking sleeve
- Dust caps available



Series 525 – DN 6.3 (1/4")



Nominal flow dia.: 6.3 mm (1/4")
Flow capacity: 29 l/min. (6.4 GPM uk)
Max. working pressure: 45 MPa
Connections: Female thread
Coupling: Steel (yellow zinc chromate plating)
Nipple: Hardened steel (yellow zinc chromate plating)

Features and other versions:

- Heavy-duty design as standard
- Double o-rings for extra sealing
- Manually extra locking feature prevents unintentional disconnection
- Dust caps available



Coupling with valve:



Nipple with valve:



Series 265 – Flat-Face (ISO 16028)



Nominal flow dia.: 6.3 mm (1/4")
Flow capacity: 12 l/min. (2.6 GPM uk)
Max. working pressure: 31.5 MPa
Connections: Female thread
Coupling: Steel (yellow zinc chromate plating)
Nipple: Hardened steel (yellow zinc chromate plating)

Features and other versions:

- Flat-face design to minimize spillage
- One-hand operated
- Extra security locking feature prevents unintentional disconnection
- Couplings feature hardened locking sleeve
- Dust caps available



Series 358 – CEJN Original Standard



Nominal flow dia.: 1.5 mm (1/16")
Max. working pressure: 60 MPa
Connections: Female/male thread
Coupling: Chrome-plated steel/brass
Nipple: Hardened steel (zink chromate plating)

Features and other versions:

- Connect under pressure up to 30 MPa
- Compact design
- High working pressure
- One-hand operated
- Dust caps included as standard
- Range of test hoses, gauges and accessories available
- Metal dust caps available



Series 415 – CEJN Original Standard



Nominal flow dia.: 8.9 mm (11/32")
Flow capacity: 61 l/min. (13.4 GPM uk)
Max. working pressure: 25 MPa
Connections: Female/male thread
Coupling: Steel (yellow zinc chromate plating)
Nipple: Hardened steel (yellow zinc chromate plating)

Features and other versions:

- One-hand operated
- High-flow capacity
- Small external dimensions
- Dust caps included as standard
- Large range of connections available
- All brass version, series 414
- Stainless steel version, series 416



Series 525 – DN 10 (3/8")



Nominal flow dia.: 10 mm (3/8")
Flow capacity: 59 l/min. (13.0 GPM uk)
Max. working pressure: 35 MPa
Connections: Female thread
Coupling: Steel (yellow zinc chromate plating)
Nipple: Hardened steel (yellow zinc chromate plating)

Features and other versions:

- Heavy-duty design as standard
- Double o-rings for extra sealing
- Coupling and nipple available with built-in pressure eliminator
- Manually extra locking feature prevents unintentional disconnection
- Dust caps available



Coupling without valve:



Nipple without valve:



Series 525 – DN 12.5 (1/2")



Nominal flow dia.: 12.5 mm (1/2")
Flow capacity: 100 l/min. (22.0 GPM uk)
Max. working pressure: 30 MPa
Connections: Female thread
Coupling: Steel (yellow zinc chromate plating)
Nipple: Hardened steel (yellow zinc chromate plating)

Features and other versions:

- Heavy-duty design as standard
- Double o-rings for extra sealing
- Coupling and nipple available with built-in pressure eliminator
- Manually extra locking feature prevents unintentional disconnection
- Dust caps available



Series 525 – DN 20 (3/4")



Nominal flow dia.: 20 mm (3/4")
Flow capacity: 194 l/min. (42.7 GPM uk)
Max. working pressure: 28 MPa
Connections: Female thread
Coupling: Steel (yellow zinc chromate plating)
Nipple: Hardened steel (yellow zinc chromate plating)

Features and other versions:

- Heavy-duty design as standard
- Double o-rings for extra sealing
- Coupling and nipple available with built-in pressure eliminator
- Manually extra locking feature prevents unintentional disconnection
- Dust caps available



Series 525 – DN 25 (1")



Nominal flow dia.: 25 mm (1")
Flow capacity: 285 l/min. (62.7 GPM uk)
Max. working pressure: 25 MPa
Connections: Female thread
Coupling: Steel (yellow zinc chromate plating)
Nipple: Hardened steel (yellow zinc chromate plating)

Features and other versions:

- Heavy-duty design as standard
- Double o-rings for extra sealing
- Coupling and nipple available with built-in pressure eliminator
- Manually extra locking feature prevents unintentional disconnection
- Dust caps available



Series 565 – Flat-Face (ISO 16028)



Nominal flow dia.: 12.5 mm (1/2")
Flow capacity: 45 l/min. (9.9 GPM uk)
Max. working pressure: 25 MPa
Connections: Female thread
Coupling: Steel (yellow zinc chromate plating)
Nipple: Hardened steel (yellow zinc chromate plating)

Features and other versions:

- Flat-face design to minimize spillage
- One-hand operated
- Extra security locking feature prevents unintentional disconnection
- Couplings feature hardened locking sleeve
- Dust caps available



Series 605 – CEJN Original Standard



Nominal flow dia.: 14.5 mm (9/16")
Flow capacity: 167 l/min. (36.7 GPM uk)
Max. working pressure: 32 MPa
Connections: Female thread
Coupling: Steel (yellow zinc chromate plating)
Nipple: Hardened steel (yellow zinc chromate plating)

Features and other versions:

- One-hand operated
- Easy connection
- High-flow capacity
- Dust caps included as standard
- Unique sealing design for max. sealing
- All brass version, series 604
- Stainless steel version, series 606



Series 665 – Flat-Face (ISO 16028)



Nominal flow dia.: 16.0 mm (5/8")
Flow capacity: 74 l/min. (16.3 GPM uk)
Max. working pressure: 25 MPa
Connections: Female thread
Coupling: Steel (yellow zinc chromate plating)
Nipple: Hardened steel (yellow zinc chromate plating)

Features and other versions:

- Flat-face design to minimize spillage
- One-hand operated
- Extra security locking feature prevents unintentional disconnection
- Couplings feature hardened locking sleeve
- Dust caps available



Series 705 – CEJN Original Standard



Nominal flow dia.: 19.0 mm (3/4")
Flow capacity: 290 l/min. (63.8 GPM uk)
Max. working pressure: 32 MPa
Connections: Female thread
Coupling: Steel (yellow zinc chromate plating)
Nipple: Hardened steel (yellow zinc chromate plating)

Features and other versions:

- One-hand operated
- Easy connection
- Dust caps included as standard
- Unique sealing design for max. sealing
- All brass version, series 904
- Stainless steel version, series 906



Series 765 – Flat-Face (ISO 16028)



Nominal flow dia.: 19.0 mm (3/4")
Flow capacity: 100 l/min. (22.0 GPM uk)
Max. working pressure: 25 MPa
Connections: Female thread
Coupling: Steel (yellow zinc chromate plating)
Nipple: Hardened steel (yellow zinc chromate plating)

Features and other versions:

- Flat-face design to minimize spillage
- One-hand operated
- Extra security locking feature prevents unintentional disconnection
- Couplings feature hardened locking sleeve
- Dust caps available



Coupling with valve:



Nipple with valve:



Coupling without valve:




Nipple without valve:





Quick Connect Couplings



Flow capacity measured at pressure drop 0.4 MPa

Series 115 – CEJN Original High-pressure Standard



Nominal flow dia.: 2.5 mm (3/32")
Flow capacity: 6.0 l/min (1.32 GPM uk)
Max. working pressure: 100 MPa
Connections: Female/male thread
Coupling: Hardened, zinc chromate plated steel
Nipple: Hardened, zinc chromate plated steel

Features and other versions:

- Compact design
- Unique patented sealing design
- Non-Drip on connection and disconnection
- Dust caps included as standard
- Nipple with hose rapture valve available
- Coupling with extra safety ring available



Series 115 – Flat-Face Version



Nominal flow dia.: 2.5 mm (3/32")
Flow capacity: 5.3 l/min. (1.16 GPM uk)
Max. working pressure: 80 MPa
Connections: Female thread
Coupling: Hardened, zinc chromate plated steel/aluminum
Nipple: (see Series 115 standard)

Features and other versions:

- Flat-face design
- Non-Drip on connection and disconnection
- Dust caps included as standard
- One-hand operated
- Automatic safety locking device
- Light weight design with an aluminum back-part
- Connects with nipple series 115 standard



Series 115/117 – High-Flow Version



Nominal flow dia.: 4.0 mm (5/32")
Flow capacity: 12.0 l/min. (3.15 GPM uk)
Max. working pressure: 70 MPa
Connections: Female/male thread
Coupling: Hardened, zinc chromate plated steel
Nipple: Hardened, zinc chromate plated steel

Features and other versions:

- High flow capacity
- Compact design
- Non-drip on connection and disconnection
- Coupling with extra safety ring available
- Dust caps included as standard



Series 116 – CEJN Original High-pressure Standard



Nominal flow dia.: 2.5 mm (3/32")
Flow capacity: 6.0 l/min. (1.32 GPM uk)
Max. working pressure: 150 MPa
Connections: Female thread
Coupling: Hardened, zinc chromate plated steel
Nipple: Hardened, zinc chromate plated steel

Features and other versions:

- High working pressure
- Compact design
- Unique patented sealing design
- Non-Drip on connection and disconnection
- Dust caps included as standard
- Nipple without valve available
- Coupling with extra safety ring available




Series 116 – Flat-Face Version



Nominal flow dia.: 2.5 mm (3/32")
Flow capacity: 5.3 l/min. (1.16 GPM uk)
Max. working pressure: 150 MPa
Connections: Female/male thread
Coupling: Hardened, zinc chromate plated steel
Nipple: (see Series 116 standard)

Features and other versions:

- Flat-face design
- Non-Drip on connection and disconnection
- Dust caps included as standard
- One-hand operated
- Automatic safety locking device
- Connects with nipple series 116 standard



Series 117 – CEJN Original High-pressure Standard



Nominal flow dia.: 2.5 mm (3/32")
Flow capacity: 6.0 l/min. (1.32 GPM uk)
Max. working pressure: 100 MPa
Connections: Female/male thread
Coupling: Hardened, zinc chromate plated steel
Nipple: Hardened, zinc chromate plated steel

Features and other versions:

- Compact design
- Unique patented sealing design
- Non-Drip on connection and disconnection
- Dust caps included as standard
- Coupling with extra safety ring available



Series 125 – CEJN Original High-pressure Standard



Nominal flow dia.: 2.5 mm (3/32")
Flow capacity: 5.8 l/min. (1.28 GPM uk)
Max. working pressure: 200 MPa
Connections: Female thread
Coupling: Hardened, zinc chromate plated steel
Nipple: Hardened, zinc chromate plated steel

Features and other versions:

- High working pressure
- Compact design
- Unique patented sealing design
- Non-Drip on connection and disconnection
- Dust caps included as standard
- Nipple without valve available



Coupling with valve:

Nipple with valve:

Coupling without valve:

Nipple without valve:

Series 135 – CEJN Original High-pressure Standard



Nominal flow dia.: 2.5 mm (3/32")
Flow capacity: 4.6 l/min. (1.01 GPM uk)
Max. working pressure: 300 MPa
Connections: Female thread
Coupling: Hardened black finished steel
Nipple: Hardened black finished steel

Features and other versions:

- Extremely high working pressure
- Non-drip on connection and disconnection
- Built-in safety device to avoid unintentional disconnection
- High safety factor
- Individual pressure testing up to max. working pressure before delivery
- Dust caps included as standard



Series 218 – CEJN Original High-pressure Standard



Nominal flow dia.: 4.5 mm (11/64")
Flow capacity: 15.0 l/min. (3.30 GPM uk)
Max. working pressure: 100 MPa
Connections: Female thread
Coupling: Hardened, zinc chromate plated steel
Nipple: Hardened, zinc chromate plated steel

Features and other versions:

- Small outside dimensions
- Extremely high-flow capacity
- High working pressure
- Compact design
- Unique patented sealing design
- Non-drip on connection and disconnection
- Built-in safety device to avoid unintentional disconnection
- Dust caps included as standard




Series 230 – (Screw-coupling)



Nominal flow dia.: 5.0 mm (3/16"), 7.0 mm (9/32")
Flow capacity: 5.0 mm – 16.1 l/min. (3.54 GPM uk)
7.0 mm – 21.2 l/min. (4.64 GPM uk)
Max. working pressure: 70 MPa
Connections: Female nipple/male coupling
Coupling: Zinc-plated steel
Nipple: Zinc-plated steel

Features and other versions:

- High-flow capacity
- Possible to connect under pressure
- Steel dust caps available



Hose and Accessories



Series 951 – High-pressure Hose

Size (IDxOD mm): 6.3x12.4, 6.3x13.3, 4.7x11.5, 4.7x13.0
Max. working pressure, MPa: 70, 100, 180, 250
Material: PA/POM with spiral wound steel wire and a PA outer sheath (may vary from size to size)

Features and other versions:

- Small outside dimensions
- Unique wear properties
- Low weight
- Small volumetric expansion
- Superior aging qualities
- Maintained flexibility through entire life
- Extensive range of end connections available
- Several different hose kits available
- 70 and 100 MPa hose available in twin designs



Series 940 – Pressure Gauges

Max. rec. working pressure: 75% of full scale
Connections: Male thread
Material: Stainless steel. Dial face of aluminum with black graduations. Gasket of polychloroprene. Window of plexiglass. Filled with glycerine.
Units: bar and PSI

Features and other versions:

- Available in three sizes;
Ø 63 mm, Ø 100 mm, Ø 160
- Max scale from 1 000 bar (14 500 PSI) to 2 060 bar (29 870 PSI)
- Durable design
- Available with bottom connection or for panel mounting



Series 950 – Adapters

Max. working pressure: from 100 up to 300 MPa
Connections: Female/male thread
Material: Black-zinc plated steel

Features and other versions:

- Extensive range of connections and threads
- Durable design
- Several seal options available



Series 950 – Porting blocks

Nom. flow dia.: 5.0 mm (3/16")
Max. working pressure: from 100 up to 300 MPa
Connections: Female thread
Material: Black-zinc plated steel

Features and other versions:

- Five different blocks available
- 2-, 3-, 4- and 5-way version
- Durable design



Coupling with valve:



Nipple with valve:



Coupling without valve:



Nipple without valve:





WEO Plug-In Hose Fittings

Save installation time and money by simply “plugging in” to hydraulic systems



WEO fittings are designed with an innovative click-to-connect feature that provides easy engagement of the product’s male and female halves, without the aid of tools or wrenches that are needed to connect and disconnect traditional threaded fittings.

Numerous additional benefits of WEO fittings make them economical connections for equipment manufacturers. These benefits include:

- **Downtime, installation time dramatically reduced**
CEJN WEO Plug-In hose fittings slash downtime and installation time for original equipment manufacturers. The click-to-connect and self-aligning features of the fittings make them easy to install in hydraulic systems.

- **Easy to connect and disconnect**
WEO fittings are designed with an innovative click-to-connect feature that provides easy engagement of the product’s male and female halves, without the aid of tools or wrenches.

- **Leak-free connections**
WEO fittings “plug in” tightly to hydraulic systems, virtually eliminated hydraulic leakage.
- **No follow-up tightening needed**
WEO fittings automatically lock into place, eliminating the need for tightening during follow-up checks.
- **Minimum space requirement enables new system designs**
WEO fittings make it easier to build compact, reliable hydraulic systems that include hose and tubes, since access for hand-tool clearance is not a requirement.

- **Work injuries associated with connection/disconnection are eliminated**

WEO fittings are quick and easy to connect and disconnect, eliminating physical injuries associated with tightening and untightening traditional threaded connections.

- **Longer hose life**

WEO fittings are self-aligning, which eliminates twisted hose that can occur during connection, and thereby extend hose life.

- **Easy to service**

The simple connection and disconnection of WEO fittings make it easy to replace hose assemblies with only a common screwdriver, even in confined or difficult-to-reach applications.

- **Lower overall cost**

The click-to-connect feature of WEO threadless fittings greatly reduces installation time for equipment manufacturers. The fittings' ability to eliminate leakage and improve accessibility also add to their lower overall cost than threaded-type fittings.

As more and more applications industry-wide are being converted from threaded to threadless connectors, WEO Plug-In hose fittings are becoming the connection of choice by well-known original equipment manufacturers for critical equipment applications.

Partnering with Hose Manufacturers

In fact, because of the industry's acceptance of CEJN threadless fittings, several international hose manufacturers have partnered with CEJN in offering their customers hose assemblies equipped with CEJN WEO products. These assemblies are of high interest to customers that are looking for a reliable, proven threadless design that is backed by a premier hose manufacturer.

As a result, more and more global customers are "plugging in" to hydraulic systems without tools or wrenches by specifying problem-solving WEO Plug-In hose fittings from CEJN.



WEO Plug-In Cartridge

The WEO Plug-In Cartridge takes the Plug-In concept one step further – right into the hydraulic component.

WEO Plug-In Cartridge is easily integrated into hydraulic components without interfering with the performance or quality. By using the integrated cartridge you get easy and effective assembly and testing, which will save cost. The innovative cartridge cuts space requirements even more by eliminating the need for adapters or female fittings.

Equipment Manufacturers

Using components with integrated WEO Plug-In cartridges will make your assembly easier and faster. You no longer need to assemble adapters or female fittings before attaching the hose or to re-tighten the hose fittings after assembly, thus also minimizing work-related injuries. The WEO Plug-In click-to-connect feature also opens up for more compact system designs. Adding up to extensive cost savings!

Component Manufacturers

Integrating the WEO Plug-In Cartridge in your components means selling and delivering cost saving benefits to your customer. With no adapters or female fittings necessary for assembly you'll also make your own testing procedures quick and easy without compromising quality. Adding up to cost savings and new business opportunities!



CEJN Multi & Auto Range

Products for Automation and Multiple Connection Lines

Quick connection and disconnection of machinery components are essential in order to keep production operations performing at peak performance and with minimum downtime.

CEJN's multi- & auto products are high-tech couplings and nipples adapted for a wide range of applications and media. Designed to be built into manifolds and plates, the different products feature such special functions as non-drip designs, connection and disconnection under full working pressure, alternative mounting features, generous misalignment capability, self-sealing couplings, corrosion resistance and high flow capacity.


Automation Couplings

The Auto-Coupling series feature a high performing coupling and nipple with a patented design allowing connection and disconnection under full working pressure. Adapted for industrial automations the auto-coupling feature a working pressure up to 300 bar (4350 PSI), a wide choice of thread connections, a non-drip design and alternative mounting functions. Available in both steel and brass constructions allows for several media applications. While the brass version is well suited for fluid applications such as water cooling lines on welding and robotic equipment and remote connection in hazardous environments the steel version is adapted for hydraulic applications like automatic tool changing systems on machine tools and engine testing equipment. Just to mention a few applications.



Multi-Snap System

The Multi-Snap is a manual push-to-connect manifold system for fluid applications. Featuring up to 8 couplings/nipples in the same manifold for simultaneous connection and disconnection. The coupling and nipple manifolds are available in a large number of sizes and connection alternatives. Both coupling and nipple are self-sealing when disconnected to prevent leakage.



Multi-Snap couplings and nipples are made of chrome-plated brass and stainless steel for long, reliable service. Multi-Snap blocks feature an aluminum construction and can be attached using common bolts.

The blocks are available with several different end connections for both couplings and nipples. The Multi-Snap range also includes such special products as connection blocks and mold hose.

Auto-Couplings for Compressed Air

The Auto-Coupling series feature a self-sealing coupling that engage with or without nipple intended for use in automatic manifold connection systems for compressed air. The unique feature of this coupling is the valve design, which allows the coupling to seal against a mating block. With features such as generous misalignment capability, reduced distance to connect, easy installation and self-sealing couplings this is an ideal product for such applications as transfer presses, tool change systems, pneumatic connections on palletizing equipment, plastic injection molding machines, robotics, automated connections of airlines.





Information of Products Available from CEJN

To obtain product information or product brochures, contact your nearest CEJN office or representative, or visit us on the Internet at www.cejn.com

>> CEJN

- General Product Range

>> Gas

- Complete Gas range

>> Fluids

- Complete Fluids range
- Non-Drip range

>> Pneumatics

- Complete Pneumatics range

>> Breathing Air

- Complete Breathing Air range

>> Hydraulics

- Complete Hydraulics range

>> High-Pressure Hydraulics

- Complete High-pressure Hydraulics range
- High-pressure Hose range

>> WEO Plug-In

- Complete WEO Plug-In range
- WEO Plug-In Cartridge range

>> Multi & Auto

- Autocouplings range
- Multi-Snap range





The Global
Quick Connect Specialist